



◀ Morbark's unique method of mounting the two hydraulic powered feed wheel drive motors provides a solid base, reducing the risk of shaft damage and leaky seals.

Beever M12R

Two dual edged, resharpenable knives are easily accessed through the flip-up chipper hood. An air impeller, located within the chipper base dramatically reduces plugging incidents.

A large feed opening allows forked limbs to enter the chipper more easily.



Designed and built in the tradition of the larger Morbark brush chippers, the Model Beaver M12R delivers more performance per pound than other competitive models in its horsepower and price range.

The Beaver M12R is a heavy duty mid-range chipper. Hydra-lift system uses live hydraulics to lift the top feed wheel for maintenance and to manually apply extra down pressure when more crushing power is required.

The 360° turnable discharge chute is height adjustable and outfitted with easily adjustable deflector with four locking positions.

Technical details:

Details:	Beever M12R
chipping principle	drum
max chipping diameter	12" (305 mm)
capacity chips	30 m ³ /h
wood chips length	19 mm
feed rate	80 FPM (24,3 MPM)
drum	Ø 508 mm, 368 mm wide
number of knives	2
vertical counterknife	1
power	51 - 115 HP
infeed opening	381 x 305 mm
funnel opening	1219 x 787 mm
feedwheel	(2) Ø 457/229 mm x 368 mm wide
weight	± 2500 kg



◀ The Beaver M12R is equipped with an automatic belt tensioner, eliminating the need for belt adjustments

Standard Equipment:

automatic feed system; hydraulic and fuel sight gauges; lockable tool box and tanks; tongue jack with stationary foot pad; variable speed flow control; self adjusting belt tensioner;

