

Beever M20R



◀ As with the Beever M18R, removing a 1" (2,54 cm) diameter pull pin is all that is to gain access to the chipper drum for routine maintenance and knife changes. The hood safety switch is activated when the hood pin is removed, disabling the engine from starting.

Standard Equipment:

automatic feed system; hydraulic and fuel sight gauges; lockable tool box and tanks; tongue jack with stationary foot pad; variable speed flow control;



◀ Auto feed is standard on the Beever M20R for maximum productivity and chipping power.



The heavy duty Beever M20R is the top model of the Morbark chipper range and it can chip up to Ø 50 cm. The Beever M20R is equipped with a 360° discharge chute and variable hydraulic down pressure on the top feed wheel.

Standard equipped with dual hydraulic rear stabilizers. Optional with a crane infeed funnel or **hydraulic folding live chain infeed floor**. All hydraulic components are powered directly from the engine, providing "live" hydraulics.

All power units from which you can choose are fully enclosed and lockable, the Beever M20R is available up to 325 horsepower. An airbraked 80 km/h undercarriage is also available for the Beever M20R.

Technical details:

Details:	Beever M20R
chipping principle	drum
max chipping diameter	20" (508 mm)
capacity chips	90 m ³ /h
wood chips length	19 mm
feed rate	110 FPM (33,5 MPM)
drum	Ø 914 mm, 724 mm wide
number of knives	6
horizontal counterknife	1
power	250 - 325 HP
infeed opening	711 x 517 mm
funnel opening	1651 x 965 mm
feedwheels	Ø 463 mm x 711 mm wide
	Ø 238 mm x 711 mm wide
weight	± 5700 - 7900 kg